## **CPI Electron Device Business - Coaxial Magnetron**



With a history of producing high quality products, we can help you with your magnetron.

Contact us at ElectronDevices@cpi-edb.com or call us at +1 978-922-6000.

## **FEATURES:**

- Frequency 9.0 9.6 GHz
- Peak power output 200 kW min.
- Duty cycle .001
- · Anode voltage 22 kV
- Anode current 28 A
- Pulsewidth 0.18 and 2.35 μs
- Heater 13.75 V @ 3.1 A
- Air cooled
- Mechanically tunable

## **BENEFITS:**

- Long life
- Exceptional frequency stability

## **APPLICATIONS:**

- Precision approach radars
- Ground controlled approach radars



Beverly Microwave Division 150 Sohier Road Beverly, Massachusetts USA 01915

tel +1 978-922-6000

email ElectronDevices@cpi-edb.com

fax +1 978-922-8914 web www.cpi-edb.com For more detailed information, please refer to the corresponding CPI EDB technical description if one has been published, or contact CPI EDB. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI EDB before using this information for system design.

©2024 CPI Electron Device Business. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI EDB.