

CPI Electron Device Business - Beacon Transponder



With a history of producing high quality products, we can help you with your beacon transponder.

Contact us at ElectronDevices@cpi-edb.com or at call us at +1 978-922-6000.

FEATURES:

- X - Band
- Peak RF power output: 800 W
- Hermetic package
- MIL -STD- 704
- MIL -STD- 461

BENEFITS:

- High stability
- Low jitter
- Rugged design for critical military aircraft use
- Production item
- Established reliability
- Compact - 3.5" x 4.5" x 2.5"
- Lightweight - 2 lbs.

APPLICATIONS:

- Beacon transponder

Typical Operating Parameters

Peak Power (kW)	Duty	Pulsewidth	Input power
800 W	0.05%	250 ns	28 VDC



Beverly Microwave Division
150 Sohier Road
Beverly, Massachusetts
USA 01915

tel +1 978-922-6000
email ElectronDevices@cpi-edb.com
fax +1 978-922-8914
web www.cpi-edb.com

For more detailed information, please refer to the corresponding CPI EDB technical description if one has been published, or contact CPI EDB. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI EDB before using this information for system design.

©2024 CPI Electron Device Business. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI EDB.