# **CPI Electron Device Business - Receiver Protector**



With a history of producing high quality products, we can help your with receiver protector.

Contact us at ElectronDevices@cpi-edb.com or at call us at +1 978-922-6000.

### FEATURES:

- Compact size
- Integral noise source

#### **BENEFITS**:

- World's largest manufacturer of receiver protectors
- High level of vertical integration
- Extensive high power test capability
- In-house environmental test facility
- Computer modeling and automatic test capabilities

### APPLICATIONS:

- Missile seekers
- Airborne radars
- Unmanned Aerial Vehicles (UAV)
- Ground based systems
- Naval radars
- Air traffic control radars
- Weather radars



## CPI EDB X-Band 2.5 W Receiver Protector: MA9905

Electrical Specificati	ions
Operating frequency	8.8 – 9.0 GHz
Maximum peakpower	2.5 kW
Maximum duty cycle	0.01
Maximum pulse width	5.0 μSec
Maximum insertion loss	1.0 dB
Maximum VSWR	1.4:1
Excess noise	16 +/ - 1 dB
Maximum spike leakagepower	1.0 W
Maximum flat leakage power	20 mW
Maximum recovery time (3 dB)	<sup>2</sup> 1.0 μSec
Maximum noise control	-14.5 +/ - 0.5 VDC

.

.

- 1

10

. .

. •

@ 100 mA

RF input	WR90	
RF output	WR90	
Noise control	Solder terminal with RFI filter	
Dimensions	See outline drawing	
Operating temperature	-30° to +75° C	
Storage temperature	-30° to +75° C	
Maximum humidity	95%	
Shock	5g/ 20 mSec	
Vibration	2 – 8 Hz, 10 mm displacement	


Mechanical and Environmental

**Specifications** 

Dimensions in inches (mm)

8 – 400 Hz, 1.3 g

DINE#SONS					
MET	INCHES		NILLMETERS		
LETTER	Ин	NAX	MN	NPAX	
A .	Z.045	2,065	31,84	52,45	
E		2.490	-	63,25	
F		1.835		41,63	
C .	1.275	1.264	32,41	32,61	
	1.218	1.22.4	30,38	51,09	
С,	nadoli,7 T	hreaded ho	-E X .433 (M	2 副型	
8	1.615	1.656	41,02	41,53	





Beverly Microwave Division 150 Sohier Road Beverly, Massachusetts USA 01915 tel +1 978-922-6000 email ElectronDevices@cpi-edb.com fax +1 978-922-8914 web www.cpi-edb.com For more detailed information, please refer to the corresponding CPI EDB technical description if one has been published, or contact CPI EDB. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI EDB before using this information for system design.

©2025 CPI Electron Device Business. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI EDB.