

CPI Electron Device Business - Microwave Power Module


The PTXM1069 is an ultra compact modular microwave power module with an integrated “super mini” travelling wave tube (TWT), a solid state preamplifier, and an optimized high density switch mode power supply.

The PTXM1069 features a broadband (6.0 to 18.0 GHz) TWT capable of providing over 140 W.

The MPM can be configured to incorporate a variety of TWT models, allowing the user to specify frequency and peak power parameters.

The MPM includes a high-speed focus electrode modulator to permit operation at high PRFs. This makes the MPM ideal for pulsed applications such as Electronic Countermeasure (ECM) and radars.

To learn more about CPI EDB’s MPM capabilities, contact CPI EDB at ElectronDevices@cpi-edb.com or call us at +44 (0)20 8573 5555



The PTXM1069 is an ultra-compact modular microwave power module with an integrated “super mini” travelling wave tube (TWT)

FEATURES:


- Frequency: 6.0 - 18.0 GHz
- Duty cycle: 100% max
- Weight: 5.3 lbs (2.4 kgs) max
- Pulswidth: 0.1 to $\infty\mu$ s

BENEFITS:

- Compact and lightweight
- Excellent thermal management
- High electrical efficiency
- High-voltage capability
- Suitable for high-altitude operations
- Resilient in high-humidity environments

APPLICATIONS:

- Radar systems
- Electronic Countermeasure (ECM) systems



RF Characteristics

Frequency range	See graph
RF output power (saturated)	See graph
Duty cycle	100 % max
Small signal gain	55 dB nom
RF input power (for saturation)	0 ± 1 dBm
Second harmonic at saturation	
6.0 – 7.0 GHz:	-3 dBc
8.0- 9.0 GHz:	-6 dBc
>9 GHz:	-8 dBc
Noise power density (Beam On)	-24 dBm/MHz max
Noise Power Density (Beam Off)	-75 dBm/MHz max
Maximum spurious PM measured in a 100 Hz bandwidth ^{Note 1}	-38 dBc - -45 dBc

Phase noise power density

-100 dBc/Hz max at 1 kHz from carrier	
-110 dBc/Hz max at 10 kHz from carrier	
-120 dBc/Hz max at >100 kHz from carrier	
Noise figure	27 dB (typical)
Input VSWR	2.0:1 max
Output VSWR	2.0:1 max (No damage)
Pulse width	0.1 to ∞ μ s (CW Operation)
Pulse delay (ON command to RF Out)	150 ns max
Pulse repetition frequency (PRF)	20 kHz max

Prime Power Requirements

Prime power	270 V DC Per MIL-STD-704E ($\pm 10\%$ normal operating range)
Power consumption	620 W maximum

Notes:

1 Other characteristics are available to special order

Connectors

Primary power input connector	Glenair: MRM18396
Control and monitoring connector	Glenair: MRM18395
RF input connector	SMA female
RF output connector	TNC female

Control and Monitoring

Control inputs	HV on, TWT beam on
Status outputs	Standby, HV on, Fault

Fault protection

Extensive internal BIT incorporated to monitor most TWT parameters. MPM shuts down under fault conditions. TWT operating parameters can be monitored externally to aid fault location.

An over-temperature trip is incorporated.

Fault outputs	Over-temperature summary fault
TWT monitor outputs	Cathode voltage, Beam current, Helix current
Heater warmup	180 seconds from power on
Automatic restart	Auto-reset after fault is included (3 restarts)

Mechanical

Mechanical outline	254.0 x 155.0 x 45.5 mm including fixings
Mechanical outline drawing	1V020806
Weight	5.3 lbs (2.4 kgs) max
Orientation	Any
Finish	Nickel plated
Markings/Labels	Type number Model number Serial number Connector ident Hazard warning
Cooling	Conduction via baseplate, +71 °C maximum temperature

Options (available on request)

Alternative prime power 28 V, 115 VAC 3-phase (plug-in or stand-alone converters)

Environmental

Temperature (operating)	-40 °C to + 71 °C
Ambient temperature (storage)	-54 °C to + 100 °C
Baseplate temperature (MPM)	+71 °C maximum collector hotspot (operating)

Altitude (operating)	0 - 40,000 ft
Vibration	0.2 g ² /Hz 10 to 40 Hz
(operating - 3 axes)	0.04 g ² /Hz 40 to 2000 Hz
Shock (3 axes)	40 g, 6 ms half sine
Humidity	MIL-STD-810D
(95 % RH non-condensing)	Method 507.2
	procedure II



CPI TMD Technologies Ltd
Swallowfield Way
Hayes, Middlesex
United Kingdom
UB3 1DQ

tel: +44 (0)20 8573 5555
email: ElectronDevices@cpiedb.com
web: www.cpi-edb.com

For more detailed information, please refer to the corresponding technical description if one has been published, or contact CPI TMD Technologies. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI TMD Technologies before using this information for system design.