VTL5341H3

L-Band 6 kW Ring Loop TWT

CPI Electron Device Business - TWT



Long life L-Band ring loop TWT. Forced air cooled at 70cfm. With a history of producing high quality products, we can help you with your TWT.

Contact us at ElectronDevices@cpi-edb.com or at call us at +1 978-922-6000.

FEATURES:

- Frequency 1.24 1.36 GHz
- Peak power output 6 kW
- Duty cycle .032
- Pulsewidth 40 µS
- Saturated gain 52 dB
- Heater 19 V @ 3.0 A
- Peak cathode voltage 11.0 kV
- Peak cathode current 2.5 A
- Grid pulsed
- Grid pulse voltage 300 Volts
- Grid bias voltage -50 Volts
- Grid current 100 mA
- Body current 800 mA

BENEFITS:

- High-power
- High gain

APPLICATIONS:

Ground-based radar



Beverly Microwave Division 150 Sohier Road Beverly, Massachusetts USA 01915

+1 978-922-6000 tel email ElectronDevices@cpi-edb.com fax +1 978-922-8914 web www.cpi-edb.com

For more detailed information, please refer to the correspond-ing CPI EDB technical description if one has been published, or contact CPI EDB. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI EDB before using this information for system design.

©2024 CPI Electron Device Business. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI EDB.