

Pressure Bypass Windows

CPI Electron Device Business - Pressure Bypass Windows



FEATURES:

- Available in L, S, C, X, Ku, and Ka-bands
- Replaceable particle filter available to extend device life
- Filter size can be specified for smaller particle size
- Waveguide configuration customizable to meet system requirements

CPI Electron Device Business has developed patented technology for pressure bypass windows with particle filtration. The pressure bypass window incorporates a waveguide pressure window with an airflow bypass through a particle filter allowing filtered air to pressurize the system.

Specifications

Frequency	L-Band	S- Band	C- Band	X- Band	Ku-Band	Ka-Band
Peak Power Handling	500 KW	500 KW	250 KW	200 KW	100 KW	50 KW
Insertion Loss	0.2 dB	0.2 dB	0.2 dB	0.2 dB	0.2 dB	0.3 dB
VSWR	1.2:1	1.2:1	1.2:1	1.25:1	1.3:1	1.4:1
Particle Filter	15 μ m	15 μ m	15 μ m	15 μ m	15 μ m	15 μ m

With a history of producing high quality products, we can help your with pressure bypass windows. Contact us at ElectronDevices@cpi-edb.com or at call us at +1 978-922-6000.



Beverly Microwave Division
150 Sohier Road
Beverly, Massachusetts
USA 01915

tel +1 978-922-6000
email ElectronDevices@cpi-edb.com
fax +1 978-922-8914
web www.cpi-edb.com

For more detailed information, please refer to the corresponding CPI EDB technical description if one has been published, or contact CPI EDB. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI EDB before using this information for system design.

©2025 CPI Electron Device Business. Company proprietary: use and reproduction is strictly prohibited without written authorization from CPI EDB.