

# CPI EDB Switch Spec Sheet

## Switch Description

For more assistance with switches contact us at  
ElectronDevices@cpi-edb.com or call us at +1 978-922-6000.

Configuration (SPST, SPDT, etc.) \_\_\_\_\_

Function (e.g. Receiver protection, TR switch, etc.)  
\_\_\_\_\_  
\_\_\_\_\_

## Desired Specifications

	MIN	MAX	UNITS
<b>Electrical</b>	_____	_____	_____
* Frequency Range	_____	_____	_____
* Peak Power	_____	_____	_____
@ Maximum Load VSWR = _____			
* Pulswewidth	_____	_____	_____
* Duty Cycle	_____	_____	_____
* Insertion Loss	_____	_____	_____
* VSWR	_____	_____	_____
* Attenuation	_____	_____	_____
* Switching Speed	_____	_____	_____
* Phase matching (if required)	_____	_____	_____
* Available bias supplies _____			
* Desired control method _____			

## Mechanical

Overall size \_\_\_\_\_

RF Connectors \_\_\_\_\_

Power/ Control Connectors \_\_\_\_\_

## Environmental

Operating temperature \_\_\_\_\_

Operating altitude \_\_\_\_\_

Other \_\_\_\_\_



**Beverly Microwave  
Division**  
150 Sohier Road  
Beverly, Massachusetts  
USA 01915

tel +1 978-922-6000  
email [ElectronDevices@cpi-edb.com](mailto:ElectronDevices@cpi-edb.com)  
fax +1 978-922-8914  
web [www.cpi-edb.com](http://www.cpi-edb.com)

For more detailed information, please refer to the corresponding CPI EDB technical description if one has been published, or contact CPI EDB. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI EDB before using this information for system design.

©2025 CPI Electron Device Business. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI EDB.