



Electron Device
Business

Military Radar Products

Reliable and Durable

**SOLID STATE
GaN POWER AMPLIFIERS**
S- to X-Band

TRANSMITTERS
S- to X-Band

**INTEGRATED MICROWAVE
ASSEMBLIES**
S-, X-, Ku- and Ka-Band

MAGNETRONS
L- to Ka-Band

COUPLED-CAVITY TWTS
S-Band

Providing global support

CPI Electron Device Business' reliable and durable products are found in radar systems around the globe

Integrated Microwave Assemblies

Receivers

- Available in these frequencies: L-, S-, C-, X-, Ku-, Ka-Bands



Absorptive High-power Integrated Assemblies

- Highly selective filter
- Low noise figures
- Fast recovery time




Digital Attenuators

- Available in frequencies: L-, S-, C-, X-, Ku-, Ka-Bands



Pulse Compressor Assemblies

- Available in frequencies: L-, S-, C-, X-, Ku-, Ka-Bands



Upconverters / Downconverters

- Available in frequencies: L-, S-, C-, X-, Ku-, Ka-Bands



High-power Integrated Assemblies

- Fast recovery time
- Low noise figures
- BITE Circuits



Integrated Front Ends

- Frequency range: 10 kW to 100 kW



Reliability and Innovation

Integral to the protection of warfighters worldwide by providing consistently reliable components for airborne, shipboard, ground, and decoy applications.

Coupled-cavity TWTs

- Up to 50 kW
- 2.4% duty
- Ground radars
- Efficient and compact
- Force air cooled



Solid State Power Amplifiers

Meets stringent specifications
Mobile and fixed-base solutions
Tried and true performance
Fielded systems with outstanding MTBF
(mean time between failures)

- Available in 1 GHz to 10.0 GHz
- Delivers greater than 300 W minimum at up to 15% duty
- Employs gallium nitride (GaN) transistor technology
- Flexible in layout and architecture



Transmitters

- Available in 1 GHz to 18 GHz
- Available in pulsed and CW (continuous wave) modes



Military Radar Products

Magnetrons

Typical Operating Parameters

Band	Frequency (GHz)	Peak Power	Duty Cycle
L	1 - 2	1 W	Various
S	2.7 - 2.9	800 kW	Various
X	8.5 - 9.6	250 kW	Various
Ku	15.6 - 16.7	40 kW	Various
Ka	32.9 - 33.5	60 kW	Various

Transmitters

Typical Operating Parameters

Band	Frequency (GHz)	Output Power	Duty Cycle
Low band	2-8 GHz	Up to 4 W	Various
High band	8-18 GHz	Up to 8 W	Various
I/J band	6-18 GHz	Up to 200 kW	CW

Solid State Power Amplifiers

Typical Operating Parameters

Band	Frequency (GHz)	Peak Power (KW)	Duty Cycle
S	2.7 - 3.0	1.3	10%
C	5.4 - 5.9	2.0	10%
X	9.0 - 10.0	1.0	10%

Coupled Cavity TWTs

Typical Operating Parameters

Band	Frequency	Output Power	Duty Cycle
S	2.75-3.05 GHz	50 kW	2.3 %

With a history of producing high-power, high quality products, we can help you with upgrading your military radar systems.

Contact us at
ElectronDevices@cpi-edb.com
 or at call us at +1 978-922-6000